

SIDE VIEW

INSTALLATION DETAILS


-GROUT

-DRAIN HOLE


SECTION A-A

DETAIL A

CLEAN CRUSHED ROCK SUMP




COVER TOP VIEW



GROUND CLAME

GROUNDING ELECTRODE WHEN SPECIFIED OR BOX HOUSES TRANSFORMER—

32



TYPICAL COVER CAPTIVE BOLT OR SIMILAR

TYPICAL THREADED INSERT OR SIMILAR

DIMENSION TABLE										
	PULL BOX					COVER				
PULL BOX	MINIMUM DEPTH BOX	MINIMUM DEPTH EXTENSION	MINIMUM WEIGHT	LI Min	WI Min	TE	D	L	w	MINIMUM WEIGHT
No. 31/2	12"	N/A	40 lb	1'- 3"	9"	1 3/4"	1 3/4"	1'-31/4" - 1'-33/8"	10" - 101/8"	30 lb
No. 5	12"	10"	55 lb	1' - 8"	11"	2"	13/4"	1'-111/4"	1'-13/4"	60 lb
No. 6	12"	10"	70 lb	2' - 41/4"	1' - 31/4"	2"	2"	2'-61/2"	1′-51/2"	85 lb
110.0	12		10 10	/4	0,4	_	_	2 0/2	. 5/2	00 15

- 1. The nominal dimensions of the opening in which the cover sets shall be the same as the cover dimensions except the length and width dimensions shall be $\frac{1}{8}$ " greater.
- 2. Covers and boxes shall be interchangeable with California standard male and female gages. When interchanged with a standard male or female gage, the top surfaces shall be flush within $\frac{1}{8}$ ". Top outside radius of covers and pull boxes shall have a $\frac{1}{8}$ " radius.
- 3. Dimensions for the cover for non-traffic pull box are nominal values.

STATE OF CALIFORNIA DEPARTMENT OF TRANSPORTATION

ELECTRICAL SYSTEMS (NON-TRAFFIC PULL BOX)

NO SCALE

ES-8A